

# WITH SEATING FOR SIX, YOU'LL CARRY THE WHOLE CREW



## RANGER 800 CREW™

### NEW! 800 TWIN EFI ENGINE




### NEW! CAB DESIGN ADDS COMFORT AND ROOM FOR SIX

All six seats in the 2010 CREW are now tilted back for extra comfort, plus both the front and rear rows have 5.1cm more legroom. New tilt steering also helps make CREW a more comfortable drive for all.



### NEW! MASSIVE STORAGE

The RANGER 800 CREW has an oversize glove box, three huge open compartments, and a space for smaller items—with more total storage than the competition. There's also an extra-large storage box (106-litre capacity) with divider slots under the seat.



### DUAL A-ARM FRONT SUSPENSION

The adjustable Dual A-Arms allow you to soak up the nastiest bumps and ruts the trail can throw at you, with virtually no harsh feedback over rugged terrain. Exclusive top mounting-point adjustability for cabs and front adjustments.

### LEGENDARY SMOOTH INDEPENDENT REAR SUSPENSION (IRS)

Our proven IRS, with the longest suspension travel in its class, keeps the ride smooth, with adjustable preload and two top-mounting points for each shock, which let you stiffen the suspension for heavy loads.

### MORE POLARIS® FEATURES

- Certified Roll-Over Protective Structure (ROPS)†
- New! Heavy-Duty front-end protection
- Tilt Steering with 25.4 cm of adjustability
- Exclusive Lock & Ride® cargo system
- Optional steel or canvas cabins
- Optional heaters, storage and winches
- Optional marine grade stereo and speakers



COMPARE THE FACTS	RANGER CREW®	MULE®* 4010 TRANS 4X4	KUBOTA®* RTV 1140 CPX
Seating	6 ✓	4	4
Top Speed	74 kmph ✓	40.2 kmph	40.2 kmph
Horsepower	40 ✓	18	25
Towing	907.2 kg ✓	544.3 kg	589.7 kg
Rear Travel	22.9 cm ✓	7.1 cm	N.A.
Ground Clearance	29.2 cm ✓	18 cm	19.1 cm
Independent Rear Suspension	Yes ✓	No	No
On-Demand True AWD	Yes ✓	No	No



\*Mule® is a registered trademark of Kawasaki Heavy Industries Inc.  
\*Kubota® is a registered trademark of Kubota Corporation.

†OSHA ROPS 29CFR1928.53

**2010**

SPECIFICATIONS

**RANGER®**

**RANGER 800 XP® (PG. 8)**

**RANGER 800 HD™ (PG. 10)**

**RANGER 800 6X6 (PG. 12)**













**RANGER 800 CREW® (PG. 14)**

Tows More, Carries More, Seats Three.

Ultimate 4x4 Lifting and Carrying.

The Heavy-Duty Leader of Modern Workhorses.

With Seating for Six, You'll Carry the Whole Crew.

		<b>RANGER 800 XP® (PG. 8)</b>	<b>RANGER 800 HD™ (PG. 10)</b>	<b>RANGER 800 6X6 (PG. 12)</b>	<b>RANGER 800 CREW® (PG. 14)</b>
S.N.A.P.	Steering Wheel or Handle Bars				
	Number of People				
	Application	 <b>WORK</b>	 <b>HD WORK</b>	 <b>HD WORK</b>	 <b>WORK</b>
ENGINE	Engine Type	<b>4-Stroke Twin Cylinder</b>	4-Stroke Twin Cylinder	4-Stroke Twin Cylinder	4-Stroke Twin Cylinder
	Displacement	<b>760cc</b>	760cc	760cc	760cc
	Fuel System	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection	Electronic Fuel Injection
	Cooling	Liquid	Liquid	Liquid	Liquid
DRIVE TRAIN	Transmission/Final Drive	Automatic PVT H/L/N/R; Shaft	Automatic PVT H/L/N/R; Shaft	Automatic PVT H/L/N/R; Shaft	Automatic PVT H/L/N/R; Shaft
	Drive System	On-Demand True AWD/2WD/Turf Mode	On-Demand True AWD/2WD/Turf Mode	<b>On-Demand True 6WD/Rear 4WD/Mid Differential Lock</b>	On-Demand True AWD/2WD/VersaTrac Turf Mode
SUSPENSION	Front Suspension	Dual A-Arm 24.4 cm Travel	Dual A-Arm 24.4 cm Travel	Dual A-Arm 24.4 cm Travel	Dual A-Arm 24.4 cm Travel
	Rear Suspension	Dual A-Arm, IRS 22.9 cm Travel	Self-Leveling Dual A-Arm, IRS 22.9 cm Travel	4-Wheel Dual A-Arm, IRS 22.9 cm Travel	Dual A-Arm, IRS 22.9 cm Travel
BRAKES	Front/Rear Brakes	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers	4-Wheel Hydraulic Disc with Dual-Bore Front Calipers
	Parking Brake	Hand-Actuated	Hand-Actuated	Hand-Actuated	Hand-Actuated
TYRES AND WHEELS	Front Tyres	25 x 10-12; 489	26 x 9-12; PXT	25 x 10-12; 489	26 x 9-12; PXT
	Rear Tyres	25 x 11-12; 489	26 x 11-12; PXT	25 x 11-12; 489	26 x 11-12; PXT
	Wheels	Stamped Steel	Aluminum	Stamped Steel	Stamped Steel
DIMENSIONS/CAPACITIES	Wheelbase	193 cm	193 cm	266.7 cm	274.3 cm
	Dry Weight	561 kg.	572 kg.	704 kg.	678 kg.
	Length/Width/Height	290 cm / 152 cm / 193 cm	290 cm / 152 cm / 193 cm	348 cm / 152 cm / 193 cm	368 cm / 152 cm / 193 cm
	Fuel Capacity	34.1 ltr.	34.1 ltr.	34.1 ltr.	34.1 ltr.
	Bed Box Dimension/Capacity	107 cm x 147 cm x 25 cm / 453.6 kg.	107 cm x 147 cm x 25 cm / 453.6 kg.	122 cm x 147 cm x 25 cm / 567 kg.	107 cm x 147 cm x 25 cm / 453.6 kg.
	Payload Capacity	<b>680.4 kg.</b>	<b>680.4 kg.</b>	<b>907.2 kg.</b>	<b>793.8 kg.</b>
	Hitch Towing Rating	<b>907.2 kg.</b>	<b>907.2 kg.</b>	<b>907.2 kg.</b>	<b>907.2 kg.</b>
	Cargo System	Lock & Ride	Lock & Ride	Lock & Ride	Lock & Ride
	Ground Clearance	30.5 cm	30.5 cm	30.5 cm	29 cm
Hitch/Type	Std/Receiver	Std/Receiver	Std/Receiver	Std/Receiver	
FEATURES	Instrumentation	Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, Hi-Temp/Low-Batt Lights, DC Outlets (2)	Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, Hi-Temp/Low-Batt Lights, DC Outlets (2)	Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, Hi-Temp/Low-Batt Lights, DC Outlets (2)	Digital Gauge, Speedometer, Odometer, Tachometer, Two Tripmeters, Hour Meter, Gear Indicator, Fuel Gauge, Hi-Temp/Low-Batt Lights, DC Outlets (3)
COLOURS	Colours	Solar Red, Sage Green, Mossy Oak Break-Up	Sage Green	Solar Red, Sage Green	Solar Red, Sage Green, Mossy Oak Break-Up